SI. No.	Description	Qty.	Unit	Rate	Rate in words	Amount
1	Fully Glazed Partitions	11.00	M ²			
	Slim line partition of approved make :- Supply and installation of full height straight glass partition 12mm thick toughened glass and proprietary electroplated as approved colour with aluminium sections of the SLIM LINE TWIN STYLE TWIN PRO SECTION NO. 6633 (35mm x 25mm) and 6634 (35mm x 20mm) male and female sections providing inside with rubber gaskets in top & bottom upto ceiling level. The glass joints shall be filled with silicon sealant on both side .Rate shall include for providing transport charges, handling, loading and unloading, Installation, protecting the module and glass till handing over, testing, commissioning all necessary hardware's, scafolding, wastage, Structural supports if any, etc. complete and all as per manufacturers specifications as directed. Etching stickers are to be provided as per design. The partition is to be firmly fixed to the floor and ceiling. The partition up to celing only be measured.					
1a	Fully Glazed Door (Single / Double Shutter)	6.00	M ²			
	Providing and fixing fully glazed door of 12 mm thick toughen glass with pencil polish edges alround with etching patterns and bevelled at edges. The door shall be fixed with DORMA patch fitting assembily inclusive of top and bottom patches, pivots, floor spring, bottom locks, SS brushed handle of 60 cm long and 2.5 cm dia. Lock of approved make etc to be fixed to the door, the edge of the glass to be polished					
2	Counter Partition (120cm (H))	20.00	M ²			
	The partitions are made of 12 mm thick glass for a height of 45 cm above the solid partition as per the drawing. The bottom portion of the partition is of double skin type for a height of 75 cm. In the frame work verticals and horizontals are made of aluminium section of 50x50x1.2 mm thick of INDAL/JINDAL as internal frame structure placed horizontally & vertically in 60x60 cm Frame work is covered with 9 mm thick marine grade plywood (IS 303) on both sides and finished with 1.0mm thick laminate of approved colour and make. The partition is firmly fixed to the					
	floor.	10.00				
3	Double Skin Solid Partition The portitions are of double plain time. The portition about her	13.00	M ²			
	The partitions are of double skin type. The partition should be firmly fixed on floor/ counter/ wall made out of aluminium section of 50x50x1.2 mm thick of INDAL/JINDAL as internal frame structure placed horizontally & vertically in 60x60 cm interval as shown in the drawing which is covered with 9 mm thick marine grade plywood(IS 303) on both sides and finished with 1 mm thick laminate of approved colour and shade on both sides . The partition is to be firmly fixed to the floor and ceiling.					

SI. No.	Description	Qty.	Unit	Rate	Rate in words	Amount
4a	Flush Door in Partitions (One Side Laminated and One Side Painted)					
	Providing and fixing 40 mm thick Flush Door using frame work made of 18 mm thick 303 Grade (BWR) Plywood, sandwiched with 6 mm thick 303 Grade (BWR) Plywood. The side facing the Banking Hall shall be finished with 1 mm thick Laminate of approved colour and make and the rear shall be finished with primer, putty and 2 coats of Enamel Paint. Vision Panel of 150 mm width shall be provided using 6 mm thick Plain Glass from 1'-0" upto 6'-0" of the door. The shutter shall be fixed to existing partition frame work using 4 no's of 4" long heavy duty SS hinges. The rates to include mortise lock with SS handle, hinges, stopper, etc.					
	Size 100x210 cm (record, toilet & meeting)	3.00	No			
	Size 90x210 cm (Store room)	1.00	No			
4b	Flush Door in Partitions (Both Side Laminated) Providing and fixing 40mm thick Flush Door using frame work	0.00	No			
	made of 18 mm thick 303 Grade (BWR) Plywood, sandwitched with 6 mm thick 303 Grade (BWR) Plywood and both sides finished with 1 mm thick Laminate of aproved colour and make. Vision Panel of 150 mm width shall be provided using 6 mm thick Plain Glass from 1'-0" upto 6'-0" of the door. The shutter shall be fixed to existing partition frame work using 4 no:s of 4" long heavy duty SS hinges. The rates to include mortise lock with SS handle, hinges, stopper, door closer etc.					
5	Fire Rated Cement Partition	15.00	M2			
	The partitions are of double skin type. The partition should be firmly fixed on floor/ counter/ wall made out of GI rectangular section of 44.5x83.5x2.5 mm thick of internal frame structure placed horizontally & vertically in 60x60 cm interval as shown in the drawing which is covered with 6 mm thick fire rated cement board on both sides finished with 2 coat putty and 2 coats of plastic emulsion paint with roller brush of approved colour to match the interior over the approved primer					
5a	Partly Glazed Door	2.50	M2			
	Door is to be provided with Aluminium frame of size 44.5x83.5x2.5 mm alround and intermediates at 60cmc/c and it is covered with 6 mm thick fire rated cement board on both sides and finished with 2 coat putty and 2 coats of plastic emulsion paint with roller brush of approved colour to match the interior over the approved primer.					
	A 8 mm thick glass is provided at a height of 75cm from bottom. Necessary Fittings such as 4Nos. 125 mm Anodised ball bearing hinges, 1No. godrej lock of approved make, 1 pair of stainless steel handle to each shutter, automatic hydraulic door closer etc. to be provided.					

	FLOOR					
SI. No.	Description	Qty.	Unit	Rate	Rate in words	Amount
6	Roller blind	10.00	M2			
	Supplying and providing zebra type roller blinds with smooth operations using manual and clutch roller controlled by a continuous cord loop. The blind is to be fixed within the window opening. The fabric shall be of sun screening quality and of approved shade. Top Roller and bottom roller to be provided with powder coated Aluminium.					
7	Notice Board	1.00	No			
	Providing and fixing notice board of size 120x90x10 cm made of 12 mm thick marine plywood back, 19 mm marine plywood sides, 6 mm thick glass front with locking arrangements. Providing Surge cloth, internal painting and finshing with 1 mm thick laminate (shade and colour as per the instruction by the Architect) etc complete.					
8	Manager Table With Side Table	1.00	No			
	Main Desk					
	Table Top- Made of 25mm thick prelaminated particle board of approved shade confirming to E1 norms. All the edges of workstation surface shall be provided with machine pressed 2mm thick imported PVC lipping glued with hotmelt Eva glue free from any VOC. Gable End and Modesty - Made of 18mm thick prelaminated particle board of approved shade confirming to E1 norms. All the edges of workstation surface shall be provided with machine pressed 2mm thick imported PVC lipping glued with hotmelt Eva glue free from any VOC.					
	Main Table Size: 160(L) X 75 (W) X 75 (H) Cms			_		
	Side Table Size : 105 (L)x 45 (W) x 75 (H) cms					
9	Modular Cubicles For Officers	5.00	No			
	Table Top- Made of 25mm thick prelaminated particle board of approved shade confirming to E1 norms. All the edges of workstation surface shall be provided with machine pressed 2mm thick imported PVC lipping glued with hotmelt Eva glue free from any VOC. Gable End and Modesty - Made of 18mm thick prelaminated particle board of approved shade confirming to E1 norms. All the edges of workstation surface shall be provided with machine pressed 2mm thick imported PVC lipping glued with hotmelt Eva glue free from any VOC.					
	Main Table Size: 150(L) X 75 (W) X 75 (H) Cms					
	Side Table Size : 105 (L)x 45 (W) x 75 (H) cms					
10	Modular Workstation For Staff	8.00	No			
	Specifications Table Top: 25mm thick Pre laminate particle board with 2mm PVC edge lipping on all exposed edges End Legs: MS powder coated legs 40x40 Intermediate Legs: MS podwer coated 60X40mm legs and supporting MS cross beams (40X20mm) Wire Management 250mm Ht Racway with 65mm Dia Wire Manager Grommet					

SI. No.	Description	Qty.	Unit	Rate	Rate in words	Amount
	Size : 120 (L) x75 (W) x 75 (H)					
11	3 Drawer Pedastal	14.00	No			
	Prelam mobile pedestal - 2D+1F with Cylindricle lock Size: 400W X 450D X 600Ht Specifications: Top & Sides: 18mm Thk pre laminated particle board Back: 9mm Thk pre laminated particle board Edge: All exposed area with 2mm thick PVC edge lipping Handle: Finger groove handle Lock: Regular lock					
12	Keyboard trays	14.00	No			
	Suppyling and fixing of keyboard trays made of HIP High -Impact -Plastic and mounted under the work top with telescopic sliding channels					
13	CPU Trolleys	14.00	No			
	Suppyling and fixing CPU trolleys made of powder coated MS sheet with adjustable width front and back open and provided with 4 adjustable castors to esae out the wire accessibility from the CPU.					
14	Back unit					
	Table Top: 18mm Thk pre laminated particle board Back: 9mm Thk pre laminated particle board with 2mm PVC edge lipping Shutters: 18mm Thk pre laminated particle board Edge: All exposed area with 2mm thick PVC edge lipping Handle: Finger groove handle Lock: Regular lock					
	(1) 127(L) X 45(W) X 75 (H) Cms	0.95	sqm			
	(2) 143(L) X 45(W) X 75 (H) Cms	1.07	sqm			
	(3) 215(L) X 45(W) X 75(H) Cms	1.61	sqm			
	(4) 195(L) X 45(W) X 75 (H) Cms	1.46	sqm			
	(5) 206(L) X 45(W) X 75 (H) Cms	1.55	sqm			
	(6) 154(L) X 45(W) X 75 (H) Cms	1.16	sqm			
	(7) 182(L) X 45(W) X 75 (H) Cms	1.37	sqm			
	(8) 154(L) X 45(W) X 75 (H) Cms	1.16	sqm			
	(9) 523(L) X 45(W) X 75 (H) Cms	3.92	sqm			
	(10) 120(L) X 45(W) X 75 (H) Cms	0.90	sqm			

SI. No.	Description	Qty.	Unit	Rate	Rate in words	Amount
15	CHAIRS					
а	Manager chair	1.00	No			
	Amaze Medium Back Mesh Chair * AN 70 Mesh*With Headrest* Self Calibrating Multilock Mechanism* Adjustable Lumbar Support* One Way Adjustable Arms (Height)* Nylon Base * Fabric Upholstered Cushion Seat					
b	Officers Chair	13.00	No			
	Comet Medium Back Mesh Chair* AN -70 Mesh* Single Lock Synchro Mechanism* One Way Adjustable Armrests (Height)* Nylon Base* Fabric Upholstered Cushion Seat					
	TOTAL(Excl. GST)					